



# Master Flow™ Pivot™ Pipe Boot Flashing

Help protect your home against damaging leaks at one of the most vulnerable parts of your new or existing roof — penetrations (the place where plumbing pipes stick through your roof)



- Durable, all-metal design helps provide tough protection at a notorious source for leaks — plumbing pipe penetrations
- Has no exposed seals or gaskets and doesn't require exposed caulking that can degrade over time when exposed to the elements
- Completely encapsulates ugly plumbing pipes for a streamlined, finished look on your new/existing roof

# Master Flow™ Pivot™ Pipe Boot Flashing



## Benefits:

- **Tough, all-metal design has no exposed seals or gaskets** and doesn't require exposed caulking that can degrade over time and cause leaks
- The Master Flow™ Pivot™ Pipe Boot Flashing **completely encapsulates ugly plumbing pipes** unlike typical seals, gaskets, or collars that leave pipes exposed
- Passes the **110 mph wind-driven rain test per TAS-100(A)** and **UL 2218 Class 4 impact-resistance test**<sup>1</sup>
- Clever ball and socket "pivot" feature allows for **simple rooftop pitch adjustment** and installation on roofs 3:12 – 12:12
- Extra-large 3" (76.2 mm) flashing on all sides helps **reduce the risk of water infiltration**
- Includes **pre-punched fastening guides** on the base flashing for ease of installation and flashing expansion/contraction
- **Pre-formed shingle termination ribs** in the base flashing help identify the cut location for shingles
- **Available in 4 colors** to help blend in with today's most popular shingle colors
- **Warranted against leaks caused by manufacturing defects or ordinary wear and tear for up to 50 years** (or as long as the warranty on the adjacent roof cladding)<sup>2</sup>
- **Enhanced warranty coverage available** when installed by a contractor certified by GAF<sup>3</sup> in connection with a qualifying roofing system<sup>4</sup>

## Models & Compatibility:

Pivot™ Model	Compatible with the following:	
	Schedule 40 PVC, ABS & Steel Plumbing Pipes (Pipe Inside Diameters)	Pipe Height (Above Roof Deck)
Pivot 1.5 PPBG1.5	1.5" (38.1 mm)	6" – 15" (152 mm – 381 mm)
Pivot 2 PPBG2	2" (50.8 mm)	
Pivot 3 PPBG3	3" (76.2 mm)	
Pivot 4 PPBG4	4" (101.6 mm)	

For more information, please contact GAF Master Flow® Technical Services at 1-800-211-9612.

Patent Pending

To learn more about the Master Flow™ Pivot™ Pipe Boot Flashing **visit [gaf.com/Pivot](https://gaf.com/Pivot)**

## Product details:

### Nominal Specifications

**Construction:** Galvanized steel

**Roof Slopes:** 3:12 – 12:12

### Plumbing Pipe Compatibility

(See chart below):

- **Pipe Types:** Schedule 40 PVC, ABS & Steel
- **Pipe Inside Diameters:** 1.5" (38.1 mm), 2" (50.8 mm), 3" (76.2 mm) & 4" (101.6 mm)
- **Pipe Heights:** 6" – 15" (152.4 mm – 381 mm) above roof deck

**Available Colors:** Black, Weathered Wood, Brown & Gray

## Complementary Colors<sup>5</sup>:



Black



Weathered Wood



Brown



Gray

<sup>1</sup> Testing performed under controlled laboratory conditions. Hail damage is not covered under GAF limited warranties.

<sup>2</sup> See GAF Master Flow™ Pivot™ Pipe Boot Flashing Limited Warranty for complete coverage and restrictions.

<sup>3</sup> Contractors enrolled in GAF certification programs are not employees or agents of GAF, and GAF does not control or otherwise supervise these independent businesses. Contractors may receive benefits, such as loyalty rewards points and discounts on marketing tools from GAF for participating in the program and offering GAF enhanced warranties, which require the use of a minimum amount of GAF products.

<sup>4</sup> See GAF System Plus, Silver Pledge™, and Golden Pledge™ Limited Warranties for complete coverage and restrictions.

<sup>5</sup> Color swatches are for reference only. Always review actual product with shingles to ensure acceptable complementary match before installation on the roof.



We protect what matters most™

